

Highlights:

- Integrated stereo audio section
- Flexible PVC jacket
- 28 AWG thin and dense stranded conductors
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Double Al-foil shielding

Product information:

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.

Components:

- CableType: SVGA215 - Audio + Video Cable



Properties:



Product Features:

Application	null
Series	null

Physical Characteristics:

Inner conductor	Insulation	Material		FPE 1.55 mm (Ø)	
		Colours		White	
Shielding		Aluminium foil		null	
		Drain wire		BC 7 x 0.12 mm (Ø) (OFC)	
Audio		Insulation	Material	PE 7540 0.7 mm (Ø)	
			Colours	Grey / Purple	
		Shielding	Spiral	CCA 28 x 0.12 mm (Ø)	
Overall shielding	Aluminium foil			null	
		Drain wire		BC 7 x 0.16 mm (Ø) (OFC)	
Outer jacket	Material			PVC 7.5 mm (Ø)	
		Colours			Black
Type of cable				75 Ω VGA video cable	
Inner conductor	Material			BC 7 x 0.12 mm (Ø) (OFC)	
Audio		Material		BC 10 x 0.12 mm (Ø) (OFC)	
Filling				Cotton Yarn	
Inner conductor	American Wire Gauge			28 AWG	
Fitted connectors				SVGA male	

Variants:

- CLV115/15 - 15 meter
- CLV115/20 - 20 meter
- CLV115/25 - 25 meter
- CLV115/30 - 30 meter